

**CONFIGURABLE OUT-OF-ORDER  
DATA TRANSFER IN A COPROCESSOR INTERFACE**

by

**Lawrence Henry Hudepohl**

**Darren Miller Jones**

**Radhika Thekkath**

**Franz Treue**

Assignee: MIPS Technologies, Inc.  
1225 Charleston Road  
Mountain View, CA 94043-1353

Address correspondence to:

James W. Huffman  
1832 N. Cascade Ave.  
Colorado Springs, CO 80907  
719.475.7103  
719.623.0141  
jim@huffmanlaw.net

00522T-425260

CONFIGURABLE OUT-OF-ORDER  
DATA TRANSFER IN A COPROCESSOR INTERFACE

by

Lawrence Henry Hudepohl

5

Darren Miller Jones

Radhika Thekkath

Franz Treue

Sub  
A5

CROSS REFERENCE TO RELATED APPLICATIONS

This application is related to U.S. Patent Application  
10 Serial No. \_\_\_\_\_ (MIPS:0104.00US) entitled  
"INSTRUCTION ISSUE GROUPS IN A COPROCESSOR INTERFACE"; U.S.  
Patent Application Serial No. \_\_\_\_\_  
(MIPS:01075.00US) entitled "HIGHLY CONFIGURABLE CO-  
PROCESSOR INTERFACE"; and U.S. Patent Application Serial  
15 No. \_\_\_\_\_ (MIPS:0108.00US) entitled "A COPROCESSOR  
INTERFACE ENABLING COPROCESSOR-SPECIFIC BRANCHING"; each of  
which are incorporated herein by reference for all  
purposes.

Sub  
A1

FIELD OF THE INVENTION

20 This invention relates in general to the field of  
computer architecture, and more specifically to an  
interface for performing out-of-order data transfers

00547-1000  
2425260

between a central processor and one or more coprocessing devices.

Sub  
A2

## BACKGROUND OF THE INVENTION

Early microprocessor based systems utilized a central  
5 processing unit, or CPU, which executed instructions, one  
at a time, in the order in which they were presented.  
These CPU's, due to their relative complexity, and  
associated cost, were typically designed to have universal  
application. That is, they were designed as general  
10 purpose CPU's.

As the use of general purpose CPU's increased, so did  
the variety of application programs they were required to  
execute. In some instances, certain programs ran extremely  
slow because they required the CPU to perform complex  
15 calculations that were really beyond the scope of what it  
was intended to perform. An example of such calculations  
included floating point operations, such a multiply,  
divide, etc.

To assist the CPU in executing such complex  
20 calculations, a floating point coprocessor was designed.  
The floating point coprocessor was essentially a second  
processor, external to the CPU, that was designed to  
perform certain complex operations such as a floating point

multiply, a floating point divide, etc, albeit much faster than the CPU. In operation, the CPU, when it was asked to perform a complex operation, would pass the operation over to the floating point coprocessor. The coprocessor would  
5 complete the task, and pass the results back to the CPU.

Although the development of the floating point coprocessor enhanced the processing speed of certain applications, its cost kept it from being added to all systems. So, many computer systems were designed around a  
10 particular CPU (e.g., an 80286), and were designed to accommodate a dedicated floating point coprocessor (e.g., an 80287), but the coprocessor was not provided with the system. If a user of the system executed the types of applications that could take advantage of the coprocessor,  
15 for an additional cost s/he could add the coprocessor to the system.

Thus, while development of the coprocessor enhanced the performance of many CPU based systems, certain design problems arose. The first is that the coprocessor and the  
20 general purpose CPU must be tightly integrated, or designed together, to allow them to communicate together effectively. Operationally speaking, the CPU must be able to detect when a program wishes to use the coprocessor, it must pass those instructions over to the coprocessor, it

must provide the data to the coprocessor that corresponds to the instructions, and it must be able to receive results back from the coprocessor. In addition, the coprocessor must know whether the CPU has been interrupted by another process, and whether it still requires the result that it is calculating. One skilled in the art will appreciate that many other issues arise relating to communications that must occur between a CPU and a coprocessor. Consequently, since the CPU and the coprocessor have to be so tightly integrated, most coprocessors that have been designed are typically designed to work with a particular CPU.

A problem that stems from the tight integration that is required between a CPU and coprocessor is that enhancement of the design of a particular CPU often requires a corresponding enhancement (or change) in the design of its associated coprocessor. For instance, an older coprocessor will typically not function with a newer CPU, and a newer coprocessor will typically not function with an older CPU. Thus, every time a CPU manufacturer wishes to introduce a new CPU, they must decide whether they want to develop a dedicated coprocessor that will work along with it. A decision to develop a coprocessor is a

very costly decision that ultimately must be supported by the marketplace.

006227 2425260  
In addition, although the above-described history of the floating-point coprocessor provides a basis for  
5 understanding that the coprocessor must be designed with a specific CPU in mind, it does not address the scope of today's coprocessing problems. Certain present day application programs require complex, time-consuming calculations that are neither appropriate for a CPU, nor  
10 for a floating-point coprocessor; i.e., other types of coprocessor's are required to optimally execute these application programs. Such programs perform 3-D rendering for graphics applications, audio/signal processing etc. But graphics coprocessors, audio coprocessors, etc., that  
15 are required to perform these special-purpose programs typically must provide a particular interface (e.g., AGP) and thus these coprocessors will only inter-operate with CPU's that are designed for that particular interface as well.

20 From the viewpoint of a system designer, choosing a particular CPU for a particular application is increasingly difficult. The designer must anticipate the future needs of the system, utilizing tightly coupled CPU/coprocessor products, without being able to select the CPU and its

097547-12900  
Docket MIPS:0105.00US

coprocessors separate from one another. For example, a designer may have requirements within an application that may be satisfied by choosing a relatively simple CPU along with a fairly complex graphics coprocessor. Regrettably, 5 the complex coprocessor today is only compatible with an equally complex (and costly) CPU. Alternatively, the designer may have requirements within an application that may be satisfied by selecting a complex CPU along with a simple coprocessor. This combination is unfortunately not 10 possible either because the complex CPU only interfaces to an equally complex (and costly) coprocessor.

Therefore, what is needed is a configurable coprocessor interface that allows a variety of CPU's to be easily coupled to a variety of different coprocessors, 15 without requiring that the coprocessors be designed specifically for those CPU's.

What is also needed is a configurable coprocessor interface that allows both forward and backward compatibility between CPU's and coprocessors. That is, a 20 coprocessor interface is desired that allows older, or legacy, coprocessors to be utilized with newer CPU's, and vice versa.

Further, what is needed is a "standardized" coprocessor interface for which CPU's and coprocessors can

be designed. Such an interface would allow a system designer to select those specific CPU and coprocessor combinations that provide an optimum solution for the designer's needs, without regard to proprietary interface requirements.

Finally, what is needed is a coprocessor interface that takes advantage of modern processing technology, such as multiple-issue of instructions, out-of-order data transfer, etc., without mandating that such technology exist in every device on the interface.

#### SUMMARY

The present invention provides a scalable and configurable coprocessor interface that distinguishes between instruction types that are transferred between a central processing unit (CPU) and a coprocessor. The configurable coprocessor interface also allows sequential or parallel transfer of differing instruction types to one or more coprocessor pipelines. In addition, the interface provides separate TO/FROM data buses between the CPU and the coprocessor to allow for simultaneous data transfer (in/out) between the CPU and the coprocessor. Furthermore, the interface provides for disassociation between instructions that are transferred, and data that is



Cont  
A7

transferred, to allow data elements to be moved in variable time slots with respect to their associated instructions. Moreover, the interface allows for out-of-order data elements to be transferred between the CPU and its

5 coprocessors in an order that is not tied to the order that associated instructions are transferred (i.e., out-of-order data transfer). Out-of-order data transfer according to the present invention does not require order tags to be associated with each data transfer. Rather, the interface

10 keeps track of the relative order of outstanding instructions that require data for execution, and provides a relative order indicator along with each piece of data as it is transferred. In addition, condition code signaling is provided from the coprocessor to allow the coprocessor

15 to evaluate CPU specific conditional instructions, and to inform the CPU as to whether or not it should execute the CPU conditional instructions.

006227 2425260

An embodiment of the present invention provides an interface for transferring data between a central

20 processing unit (CPU) and a plurality of coprocessors. The interface includes an instruction bus and a data bus. The instruction bus transfers instructions to the plurality of coprocessors in an instruction transfer order, where particular instructions direct designated ones of the

A7

plurality of coprocessors to transfer the data to/from the CPU. The data bus is coupled to the instruction bus. The data bus subsequently transfers the data, where data order signals within the data bus prescribe a data transfer order

5 that differs from the instruction transfer order.

00651747-122000

In another aspect, the present invention provides a computer program product for use with a computing device, the computer program product has a computer usable medium that includes computer readable program code embodied

10 thereon. The computer readable program code causes a coprocessor interface to be described that transfers data between CPU and a plurality of coprocessors. The computer readable program code has first program code and second program code. The first program code provides an

15 instruction bus, where the instruction bus is configured to transfer instructions to the plurality of coprocessors in an instruction transfer order, and where particular instructions direct designated ones of the plurality of coprocessors to transfer the data to/from the CPU. The

20 second program code provides a data bus. The data bus is configured to subsequently transfer the data, where data order signals within the data bus prescribe a data transfer order that is different from the instruction transfer order.

A7  
In a further aspect, the present invention provides a computer data signal embodied in a transmission medium. The computer data signal has computer-readable first program code and computer-readable second program code.

5 The computer-readable first program code provides an instruction bus for transferring instructions to a plurality of coprocessors in an instruction transfer order, where particular instructions direct particular coprocessors to transfer data to/from a CPU. The computer-  
10 readable second program code provides a data bus for subsequently transferring the data, where data order signals within the data bus prescribe a data transfer order that differs from the instruction transfer order.

00622T 242560  
In yet another aspect, the present invention provides  
15 a method for transferring data between a CPU and a plurality of coprocessors. The method includes transmitting instructions to the plurality coprocessors, each of the instructions directing a data transfer between the CPU and a specific coprocessor, where the transmitting  
20 is provided in a specific instruction order; and subsequently transferring the data in an order different from the specific instruction order. The transferring includes prescribing transfer of a data element corresponding to a specific outstanding instruction

A7  
relative to all outstanding instructions, the outstanding instructions being those instructions that have not completed a subsequent data transfer.

Other features and advantages of the present invention will become apparent upon study of the remaining portions of the specification and drawings.

Sub A3 **BRIEF DESCRIPTION OF THE DRAWINGS**

FIGURE 1 is a block diagram of a central processing unit (CPU) coupled to a coprocessor utilizing the coprocessor interface of the present invention.

FIGURE 2 is a flow chart illustrating instruction flow through the CPU and coprocessor of Figure 1.

FIGURE 3 is a block diagram illustrating instruction dispatch signals between a CPU and a coprocessor utilizing the coprocessor interface of the present invention.

FIGURE 4 is a timing diagram illustrating how instructions are dispatched on the coprocessor interface of the present invention.

FIGURE 5 is a timing diagram illustrating how multiple instructions are dispatched to multiple issue groups via the coprocessor interface of the present invention.

FIGURE 6 is a timing diagram illustrating how the coprocessor delays instruction dispatch from the CPU

utilizing busy signals on the coprocessor interface of the present invention.

FIGURE 7 is a block diagram illustrating coprocessor to/from data transfer instruction signals between a CPU and  
5 a coprocessor utilizing the coprocessor interface of the present invention.

FIGURE 8 is a timing diagram illustrating how data is transferred from a CPU to a coprocessor utilizing the coprocessor interface of the present invention.

10 FIGURE 9 is a timing diagram illustrating how data is transferred from a coprocessor to a CPU utilizing the coprocessor interface of the present invention.

FIGURE 10 is a block diagram illustrating coprocessor interface signals for: 1) coprocessor condition code  
15 checks; 2) CPU general purpose register values; 3) exception signal from a coprocessor to the CPU; and 4) instructions commit signaling from a CPU to a coprocessor, according to the present invention.

FIGURE 11 is a timing diagram illustrating how a  
20 coprocessor responds to a CPU with condition code checks, according to the present invention.

FIGURE 12 is a timing diagram illustrating exception handling between a CPU and a coprocessor utilizing the coprocessor interface of the present invention.

FIGURE 13 is a timing diagram illustrating an instruction commit procedure by a CPU coupled to a coprocessor utilizing the coprocessor interface of the present invention.

5

Sub  
24

# DETAILED DESCRIPTION

Referring to Figure 1, a portion of a computing system 100 is shown. The computing system 100 provides a central processing unit (CPU) 102 coupled to memory 120 via a system bus 118. In general, the CPU 102 executes instructions retrieved from the memory 120, and interfaces with other devices 124 that are external to it via an I/O interface 122 attached to the system bus 118.

The CPU 102 is also coupled to a coprocessor 110 utilizing a coprocessor interface according to the present invention. The coprocessor 110 may be any type of coprocessor, but most commonly is a floating-point coprocessor, or a graphics (3-D) coprocessor. As will be more fully described below, with reference to Figure 2, the CPU 102 retrieves instructions from the memory 120, and determines whether the instructions are directed to it, or to the coprocessor 110. If the instructions are to be directed to the coprocessor 110, they are provided using the coprocessor interface of the present invention.

Within the CPU 102 are a bus interface 104, a cache system 106, an execution core 108, and a coprocessor interface 112a. The bus interface 104 is coupled to the system bus 118 for retrieving and storing instructions and data, from and to the memory 120, and for communicating with the other devices 124. Data and instructions retrieved by the bus interface are provided to the cache system so that they may be immediately accessible to the execution core 108. The execution core 108 executes instructions provided to it by the cache system 106, operating on data that is either resident within the cache system 106, or retrieved by the bus interface 104.

In one embodiment, the execution core 108 is split into two (or more) execution units (designated A & B), each capable of executing instructions directed to the CPU 102. That is, two (or more) instructions may be provided to the execution units A & B, within the execution core 108, for simultaneous execution.

The execution core 108 is coupled to a coprocessor interface (COP interface) 112a. The COP interface 112a enables coprocessors such as floating point units (FPU's) and Graphics Engines to be tightly coupled to an integer processor core such as the execution core 108. In one embodiment, the COP interface 112a is designed to allow

coprocessors to interface with various processor cores designed by MIPS Technologies, of Mountain View, California.

00637 475260

The COP interface 112a includes many features, each of which will be further described below, with reference to Figures 3-14. More specifically, the COP interface 112a allows 32-bit or 64-bit data transfer between an integer core and a coprocessor. In addition, the COP interface 112a supports one or more coprocessors, each of which may have one or more execution units. The COP interface 112a allows between 0 and 8 out-of-order data transfers. And, the COP interface 112 allows either single-issue of instructions, or multiple instruction issue, to one or more coprocessors, where each issue supports arithmetic and/or data transfers. Furthermore, as will be more particularly described with reference to Figure's 10, 11, and 13, the COP interface 112 allows for user defined exceptions, and coprocessor defined condition code interpretation. Finally, the COP interface 112a is designed to support coprocessor instructions defined in the MIPS32, MIPS64, MDMX and MIPS-3D architecture specifications available from MIPS Technologies, Inc.. Of course, one skilled in the art will appreciate that the novel features of the COP interface 112a are not restricted to data size, instruction



set architecture, etc. Rather, the COP interface 112a is applicable to any interface between a CPU and a coprocessor where the design considerations include scalability, compatibility (both forward and backward), and/or  
5 configurability.

As shown in Figure 1, the COP interface 112a within the CPU 102 is coupled to a coprocessor 110 via coprocessor interface signal lines 116. Within the coprocessor 110 are a COP interface 112b and an execution unit 114. The COP  
10 interface 112b is similar to the COP interface 112a, but is designed to communicate from the coprocessor 110 to the CPU 102. The execution unit 114 may either be a single-issue execution unit, or may be split into two (or more) execution units A and B for simultaneous execution of  
15 multiple coprocessor instructions.

Operation of the computing system 100 will now be described with respect to the flow of instruction execution by reference to the flow chart 200 of Figure 2, to which attention is now directed.

20 Instruction flow begins when instructions are fetched 202 by the execution core 108. That is, a program counter (not shown) contains an address related to the next instruction to be executed. This address is provided to the cache system 106 for determination of whether the

instruction is resident within the cache system 106. If it is not, the instruction is first fetched from the memory 120, by the bus interface 104 and is provided to the execution core 108. Once the instruction is provided to  
5 the execution core 108, the instruction flow proceeds to the decode block 204.

At decode block 204, the execution core decodes the instruction to be executed. That is, the decode block performs a variety of decoding functions, including  
10 determining whether the instruction is a branch instruction, and if so, predicting whether the branch will be taken, determining what operands are necessary for execution of the instruction, etc. Instruction flow then proceeds to decision block 206.

15 At decision block 206, the execution core 108 determines whether the instruction to be executed is an integer instruction to be executed by the execution core 108, or whether the instruction is a coprocessor instruction to be executed by the execution unit 114. If  
20 the instruction is an integer instruction, instruction flow proceeds to block 208. Otherwise, the execution core 108 provides the coprocessor instruction to the COP interface 112a. The COP interface 112a then presents the coprocessor instruction, and any associated data for the instruction,

to the coprocessor 110 for execution. Instruction flow then proceeds to block 212.

At block 208, the execution core 108 executes the integer instruction. Instruction flow then proceeds to  
5 block 210 where the result of the execution, if any, is written back into a register (or memory location) within the CPU 102.

At block 212, the COP interface 112b receives the coprocessor instruction from the CPU 102 for execution.  
10 The coprocessor instruction, and its associated data, are provided to the execution unit 114 for execution. The result of the execution remains in the coprocessor 110 until future instructions request that the result be transferred to the CPU 110.

15 The above discussion, with reference to Figure's 1 and 2 provides a general understanding of an interface between a CPU 102 and a coprocessor 110, utilizing the coprocessor interface 112 of the present invention. With the above in mind, particular operational specifics of the COP interface  
20 112 of Figure 1 will now be described with reference to Figures 3-14 by description of specific interface signals within the COP interface 112, and their operation with respect to such functions as instruction transfers, data TO transfers, data FROM transfers, etc.

### Instruction Transfer

Instruction transfer refers to how coprocessor instructions are provided from a CPU to a coprocessor. Table 1 below provides a brief summary of some of the instruction transfer signals that are provided within the COP interface of the present invention. Illustration of how these signals operate will be further described below with reference to Figure's 3-6.

**TABLE 1**

| Signal Name   | Dir | Issue Group     | Description                                                                                                                                                                                                                                                                                                                                                               |
|---------------|-----|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CP_ir_m[31:0] | Out | Comb, Arith, TF | <b>Coprocessor Instruction Word.</b> Valid in the cycle before CPx_as_m, CPx_ts_m, CPx_fs_m is asserted.                                                                                                                                                                                                                                                                  |
| CPx_as_m      | Out | Comb, Arith     | <b>CoprocessorX Arithmetic Instruction Strobe.</b> Asserted in the cycle after an arithmetic coprocessorX instruction is available on CP_ir_m. If CPx_abusy_m was asserted in the previous cycle, this signal will not be asserted. In any cycle, at most 1 of the following signals can be asserted at a time in a particular issue group. CPx_as_m, CPx_ts_m, CPx_fs_m. |
| CPx_abusy_m   | In  | Comb, Arith     | <b>CoprocessorX Arithmetic Busy.</b> When asserted, a coprocessorX arithmetic instruction will not be dispatched. CPx_as_m will not be asserted in a cycle after the signal is asserted.                                                                                                                                                                                  |
| CPx_ts_m      | Out | Comb, TF        | <b>CoprocessorX to Str obe.</b> Asserted in the cycle after a To COPx Op instruction is available on CP_ir_m. If CPx_tbusy_m was asserted in the previous cycle, this signal will not be asserted. In any cycle, at most 1 of the following signals can be asserted at a time in a particular issue group: CPx_as_m, CPx_ts_m, CPx_fs_m.                                  |
| CPx_tbusy_m   | In  | Comb, Arith     | <b>To CoprocessorX Busy.</b> When asserted, a To COPx Op instruction will not be dispatched. CPx_ts_m will not be asserted in a cycle after the signal is asserted.                                                                                                                                                                                                       |

| Signal Name     | Dir | Issue Group     | Description                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------|-----|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPx_fs_m        | Out | Comb, TF        | <b>CoprocessorX From Strobe.</b> Asserted in the cycle after a From COPx Op instruction is available on CP_ir_m. If CPx_fbusy_m was asserted in the previous cycle, this signal will not be asserted. In any cycle, at most 1 of the following signals can be asserted at a time in a particular issue group: CPx_as_m, CPx_ts_m, CPx_fs_m.                                                                              |
| CPx_fbusy_m     | In  | Comb, Arith     | <b>From CoprocessorX Busy.</b> When asserted, a From COPx Op instruction will not be dispatched. CPx_fs_m will not be asserted in a cycle after the signal is asserted.                                                                                                                                                                                                                                                  |
| CP_order_m[2:0] | Out | Comb, Arith, TF | <b>Coprocessor Dispatch Order.</b> Signifies the program order of instructions when more than one instruction is issued in a single cycle. Each instruction dispatched has an order value associated with it. There must always be one instruction whose order value is 0. Order values must increment by 1 when more than one instruction is issued in a cycle. Valid when CPx_as_m, CPx_ts_m, or CPx_fs_m is asserted. |
| CP_VNs_m        | Out | Comb, Arith, TF | <b>Coprocessor Valid or Null Strobe.</b> Asserted when a valid or null signal is available on CP_VN_m.                                                                                                                                                                                                                                                                                                                   |
| CP_VN_m         | Out | Comb, Arith, TF | <b>Valid or Nullify Coprocessor Instruction.</b> When deasserted, the integer processor core is signaling that the instruction is valid, i.e., not nullified. When asserted, the integer processor core is signaling that the instruction is nullified. Valid when CP_VNs_m is asserted.                                                                                                                                 |

Signal names in Table 1, and in the other tables that follow should be interpreted as follows:

Signal names beginning in CP\_ relate to signals from a CPU to any/all coprocessors coupled to the CPU. Signal names beginning in "CPx\_" are specific to particular coprocessors attached to the CPU. That is, if two coprocessors are attached to a CPU, two sets of signal lines will be provided by the coprocessor interface within the CPU. The first set of signal lines will begin "CP1\_",

the second set of signal lines will begin "CP2\_", etc. Rather than illustrate separate signals for CP1 and CP2, they have been combined in the present discussion as "CPx" for purposes of clarity. Note: in one embodiment, within  
5 the context of the MIPS architecture, the only valid coprocessors are CP1 and CP2.

In addition, instruction types have been designated as arithmetic (a), data TO coprocessor (t), or data FROM coprocessor (f). So, arithmetic signal names include the  
10 letter "a", TO signal names include the letter "t", and FROM signal names include the letter "f". By distinguishing between arithmetic, data to, and data from instructions, the coprocessor interface of the present invention allows coprocessors to disable certain types of  
15 instructions, within particular issue groups.

The ending designation "\_m" designates a particular issue group. The coprocessor interface of the present invention is extensible to support both single-issue and multi-issue cores and coprocessors. That is, a single  
20 issue CPU can support one or more multi-issue coprocessors. Alternatively, a multi-issue CPU can utilize single or multi-issue coprocessors. Multi-issue support is achieved by duplicating certain signals of the coprocessor interface. Thus, if support of single-issue is desired,

5

10

20

Figure 4 provides a timing diagram 400 illustrating a simple case of instruction transfer. That is, three coprocessor instructions A, B & C will be transferred by the CPU 302 to the coprocessor 310. All of the signals shown in Figure 4 are synchronous with respect to a common clock signal generated by the CPU 302. In one embodiment, the clock signal is the core frequency signal of the CPU 302.

At clock cycle 2, a coprocessor instruction A has been placed by the coprocessor interface 312 within the CPU 302 on CP\_ir\_m[31:0]. This instruction is an arithmetic instruction, such as an ADD, MULTIPLY, DIVIDE, but may be another type of instruction defined within the arithmetic group. In addition, this instruction is in the issue group designated by "\_m". At the beginning of clock cycle 2, it is said that instruction A has been dispatched by the coprocessor interface 312.

After an instruction is dispatched, additional information about that instruction must be transferred between the CPU 302 and the coprocessor 310. Such information includes the type of instruction (a, t, or f), an indication of which coprocessor the instruction is destined for (CP1, CP2, etc.), and the issue group to which the instruction belongs (0, 1, 2 ...).



At clock cycle 3, the coprocessor interface 312 asserts the instruction dispatch strobe signal CPx\_as\_m to indicate to the coprocessor 310 that the instruction dispatched during the previous cycle should be used by the  
5 coprocessor as an active instruction, and that it was an arithmetic instruction. It is possible that the instruction dispatch strobe signal may be asserted in the same cycle as the instruction dispatch.

Each such transfer can occur as early as one cycle  
10 after instruction dispatch, with no maximum limit on how late the transfer can occur. That is, only the dispatch portion of the coprocessor interfaces have flow control. In addition, the coprocessor interface 312 is designed to operate with coprocessors of any pipeline structure and  
15 latency. If the CPU 302 requires a specific transfer by a certain cycle, the CPU 302 must stall until the transfer has completed. In addition, all transfers are strobed. That is, independent of strobing, data is transferred in the cycle that the strobe signal is asserted. If the  
20 strobe signal is asserted for 2 cycles, then two transfers occur.

At clock cycle 4, an instruction B is dispatched on signal lines CP\_ir\_m.

5

10

15

## 20

t

signals within the coprocessor interface 312 must occur so that the coprocessor 310 knows when it can begin operation of subsequent operations that depend on the result of the current instruction. Validity or Nullification must be performed in an early stage of the coprocessor 310's pipeline to insure that subsequent instructions can begin with correct operands.

Referring to Figure 4, on clock cycle 4, the coprocessor interface 312 asserts strobe signal CP\_VNs\_m. This assertion corresponds to a validity/nullification transfer for instruction A. Also during clock cycle 4, the coprocessor interface 312 deasserts signal CP\_VN\_m to indicate that instruction A is valid and should not be nulled.

On clock cycle 5, the coprocessor interface 312 continues to assert strobe signal CP\_VNs\_m, and continues to deassert signal CP\_VN\_m to indicate that instruction B is valid.

On clock cycle 8, the coprocessor interface 112 asserts strobe signal CP\_VNs\_m corresponding to a validity or nullification transfer for instruction C. Also during clock cycle 8, the coprocessor interface 312 asserts signal CP\_VN\_m to indicate to the coprocessor that instruction C should be nulled.

Thus, instruction validity or nullification continues for all instructions transferred between the CPU 302 and the coprocessor 310. There is no tag or other identification relating a validity or nullification signal on CP\_VN\_m with an instruction. Rather, since the instructions are in-order, the coprocessor interfaces within both the CPU 302 and the coprocessor 310 keep track of each transferred instruction, and do not allow an instruction to use operands generated by previous instructions until those previous instructions have received a CP\_VN\_m signal. In addition, if an instruction is nullified, no remaining transfers for that instruction will occur. If a transfer related to a nullified instruction occurs during the cycle of nullification, the transfer will be ignored.

#### ***Instruction Ordering – Multiple Issue Groups***

Referring now to Figure 5, a timing diagram 500 is provided to particularly illustrate how instructions are transferred to multiple issue groups. In this timing diagram, it is presumed that the CPU 302 is a dual issue integer processor. The coprocessor 310 is also a dual issue coprocessor. The two issue pipes within the coprocessor 310 are designated as \*\_0 and \*\_1,

respectively. And, the coprocessor interfaces 312 of both the CPU 302 and the coprocessor 310 include interface signals corresponding to each of the two issue groups.

In clock cycle 1, two instructions A and B are  
5 dispatched by the coprocessor interface 312 within the CPU 302. Instruction A appears on signal lines CP\_ir\_0 corresponding to the first issue group (or pipe within coprocessor 310). Instruction B appears on signal lines CP\_ir\_1 corresponding to the second issue group (or pipe  
10 within coprocessor 310).

During clock cycle 2, the coprocessor interface 312 within the CPU 302 asserts strobe line CP1\_as\_0 to designate instruction A as an arithmetic instruction, to indicate to the coprocessor 310 that it is the target  
15 coprocessor for the instruction (i.e., CP1), to indicate that the pipe for which instruction A is intended is the "0" pipe, and to complete the transfer of instruction A to the coprocessor. Additionally, the coprocessor interface 312 within the CPU 302 asserts strobe line CP1\_ts\_1 to  
20 designate instruction B as a TO coprocessor data transfer instruction, to indicate to the coprocessor 310 that it is the target coprocessor for the instruction (i.e., CP1), to indicate that the pipe for which instruction B is intended is the "1" pipe, and to complete the transfer of

instruction B to the coprocessor. While not shown, it should be appreciated that instruction validity or nullification also occurs during later clock cycles, similar to that illustrated in Figure 4.

5        Also during clock cycle 2, instruction order signals are presented by the coprocessor interface 312 to the coprocessor 310 to indicate the programming order of instructions A and B. That is, even though instructions A and B are presented in parallel to the two instruction  
10    pipes "0" and "1" within the coprocessor 310, an indication must be presented to the coprocessor 310 to indicate their original order with respect to the program. Such order indication is necessary to insure that the coprocessor 310 resolves any dependencies between the instructions  
15    correctly.

Thus, each issue group carries an order signal to indicate the order of the instruction in that issue group with respect to the others. Two signal groups are provided between the CPU 302 and the coprocessor 310, corresponding  
20    to the two execution pipes within the coprocessor 310. The first signal group is CP\_order\_0, corresponding to the "0" pipe. The second signal group is CP\_order\_1, corresponding to the "1" pipe. Thus, during clock cycle 2, at the time instructions A and B are transferred by the strobe signals,

the relative order of instructions A and B are designated by the two signal groups. More specifically, signal group CP\_order\_0 indicates to the "0" pipe in the coprocessor 310, that the instruction transferred to it, i.e., instruction A, is the first instruction, having a relative order of "0". And, signal group CP\_order\_1 indicates to the "1" pipe in the coprocessor 310 that the instruction transferred to it, i.e., instruction B, is the second instruction, having a relative order of "1".

During clock cycle 4, two more instructions, C and D are dispatched by the coprocessor interface 312 within the CPU 302 to the coprocessor 310. Instruction C is dispatched on signal group CP\_ir\_1 indicating that it is intended for the "1" pipe of coprocessor 310, and instruction D is dispatched on signal group CP\_ir\_0 indicating that it is intended for the "0" pipe of coprocessor 310. Note, if more than two coprocessors are coupled to the coprocessor interface 312 of the CPU 302, then the transfer of the dispatched instructions is designated by the strobe signals associated with each of the coprocessors (e.g., CP1 vs. CP2).

During clock cycle 5, transfer of instruction C to pipe "1" of the coprocessor 310 is completed by assertion of strobe line CP1\_as\_1. Assertion of this strobe line

indicates that instruction C is an arithmetic instruction, and that it is directed to coprocessor CP1, in its "1" pipe. Also, transfer of instruction D to pipe "0" of the coprocessor 310 is completed by assertion of strobe line  
5 CP1\_ts\_0. Assertion of this strobe line indicates that instruction D is a TO coprocessor data transfer instruction, and that it is directed to coprocessor CP1, in its "0" pipe.

Also during clock cycle 5, the relative order of  
10 instructions C and D are provided to the coprocessor 310 via signal groups CP\_order\_0, and CP\_order\_1. Signal group CP\_order\_1 designates that instruction C is the first instruction, by providing a relative order quantity of "0" to the coprocessor 310. Signal group CP\_order\_0 designates  
15 that instruction D is the second instruction, by providing a relative order quantity of "1" to the coprocessor 310.

During clock cycle 6, instruction E is dispatched by the coprocessor interface 312 to the coprocessor 310.

During clock cycle 7, instruction E transfer is  
20 completed by assertion of strobe line CP1\_as\_0. This strobe line indicates that instruction E is designated for coprocessor CP1, that the instruction is an arithmetic instruction, and that it should be executed by the "0" pipe. Since instruction E was the only instruction



dispatched during clock cycle 6, its relative dispatch order is provided by signal group CP\_order\_0 as "0".

Also during clock cycle 7, instruction F is dispatched by the coprocessor interface 312 to the "1" pipe of the  
5 coprocessor 310.

During clock cycle 8, instruction F transfer is completed by assertion of strobe line CP1\_ts\_1. This strobe line indicates that instruction F is designated for coprocessor CP1, that the instruction is a T0 coprocessor  
10 data transfer instruction, and that it should be executed by the "1" pipe. Since instruction F was the only instruction dispatched during clock cycle 7, its relative dispatch order is provided by signal group CP\_order\_1 as "0".

15 Although not particularly illustrated, one skilled in the art should appreciate that by providing a 3-bit signal group for each available issue group, up to 8 instructions may be dispatched at the same time, while still tracking their relative order for instruction execution.

## 20 ***Instruction Transfer – Coprocessor Busy***

Referring now to Figure 6, a timing diagram 600 is shown which particularly illustrates the operation of various busy signals available on the coprocessor interface

of the present invention. More specifically, each coprocessor that is coupled to a CPU may reach a point during execution of instructions such that it can't receive further instructions. Within the coprocessor interface of

5 the present invention, busy signals are provided from the coprocessor to the CPU for each of the instruction types (a, t and f), for each available issue group.

During clock cycle 1, an instruction A is dispatched on signal group CP\_ir\_0. Also during cycle 1, a busy

10 signal is asserted by coprocessor CPx on signal line CPx\_tbusy\_m. Assertion of this signal line indicates to the coprocessor interface 312 within the CPU 302 that coprocessor CPx cannot receive a TO coprocessor data instruction.

15 During clock cycle 2, instruction A transfer is completed by assertion of strobe line CPx\_as\_m. That is, although the coprocessor 310 asserted a busy signal, the busy portion of the coprocessor was related to TO coprocessor data instructions, not to arithmetic

20 instructions. So, instruction A dispatch is attempted and transferred.

During clock cycle 3 instruction B is dispatched by the coprocessor interface 312. However, busy signals are being asserted by both the arithmetic and TO coprocessor

Also, during clock cycle 3, the arithmetic busy signal is deasserted. Since instruction B continues to be dispatched by the coprocessor interface 312, it appears that instruction B is not an arithmetic instruction.

During clock cycle 6, instruction B transfer is completed by assertion of strobe CPx\_ts\_m. Also during clock cycle 6, instruction C is dispatched by the coprocessor interface 312 within the CPU 302.

During clock cycle 8, a busy signal is asserted on signal line CPx fbusy\_m to indicate that during cycle 8,

the coprocessor 310 cannot receive another FROM data transfer instruction.

What should be appreciated from the above is that at any time during execution of instructions by a coprocessor, should that coprocessor's resources become consumed, within a particular group (a, t, or f), the coprocessor can prevent further instructions from being transferred that are specific to the particular group, without affecting transfer of instructions to other groups.

10 ***To/From Coprocessor Data Transfer***

To/From data transfer refers to how data, corresponding to previously transferred instructions is provided from a CPU to a coprocessor, and vice versa. Table 2 below provides a brief summary of some of the data transfer signals that are provided within the COP interface of the present invention. Illustration of how these signals operate will be further described below with reference to Figure's 7-9.

TABLE 2

| Signal Name                                                 | Dir                                            | Issue Group | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|-------------------------------------------------------------|------------------------------------------------|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|-------|--------|--------------------------------------------|--------|------------------------------------------------|--------|------------------------------------------------|--------|------------------------------------------------|--------|------------------------------------------------|--------|------------------------------------------------|--------|------------------------------------------------|--------|------------------------------------------------|
| To Coprocessor Data (For all To Coprocessor Operations)     |                                                |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
| CP_tds_m                                                    | Out                                            | Comb, TF    | <b>Coprocessor To Data Strobe.</b> Asserted when To COP Op data is available on CP_tdata_m.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
| CP_torder_m[2:0]                                            | Out                                            | Comb, TF    | <b>Coprocessor To Order.</b> Specifies which outstanding To COP Op the data is for. Valid only when CP_tds_m is asserted.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|                                                             |                                                |             | <table><tr><th>CP_torder_m</th><th>Order</th></tr><tr><td>3'b000</td><td>Oldest outstanding to COP Op data transfer</td></tr><tr><td>3'b001</td><td>2<sup>nd</sup> oldest To COP OP data transfer</td></tr><tr><td>3'b010</td><td>3<sup>rd</sup> oldest To COP OP data transfer</td></tr><tr><td>3'b011</td><td>4<sup>th</sup> oldest To COP OP data transfer</td></tr><tr><td>3'b100</td><td>5<sup>th</sup> oldest To COP OP data transfer</td></tr><tr><td>3'b101</td><td>6<sup>th</sup> oldest To COP OP data transfer</td></tr><tr><td>3'b110</td><td>7<sup>th</sup> oldest To COP OP data transfer</td></tr><tr><td>3'b111</td><td>8<sup>th</sup> oldest To COP OP data transfer</td></tr></table> | CP_torder_m                                    | Order | 3'b000 | Oldest outstanding to COP Op data transfer | 3'b001 | 2 <sup>nd</sup> oldest To COP OP data transfer | 3'b010 | 3 <sup>rd</sup> oldest To COP OP data transfer | 3'b011 | 4 <sup>th</sup> oldest To COP OP data transfer | 3'b100 | 5 <sup>th</sup> oldest To COP OP data transfer | 3'b101 | 6 <sup>th</sup> oldest To COP OP data transfer | 3'b110 | 7 <sup>th</sup> oldest To COP OP data transfer | 3'b111 | 8 <sup>th</sup> oldest To COP OP data transfer |
|                                                             |                                                |             | CP_torder_m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Order                                          |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|                                                             |                                                |             | 3'b000                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Oldest outstanding to COP Op data transfer     |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|                                                             |                                                |             | 3'b001                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 2 <sup>nd</sup> oldest To COP OP data transfer |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|                                                             |                                                |             | 3'b010                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 3 <sup>rd</sup> oldest To COP OP data transfer |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|                                                             |                                                |             | 3'b011                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 4 <sup>th</sup> oldest To COP OP data transfer |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|                                                             |                                                |             | 3'b100                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 5 <sup>th</sup> oldest To COP OP data transfer |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|                                                             |                                                |             | 3'b101                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 6 <sup>th</sup> oldest To COP OP data transfer |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
|                                                             |                                                |             | 3'b110                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 7 <sup>th</sup> oldest To COP OP data transfer |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
| 3'b111                                                      | 8 <sup>th</sup> oldest To COP OP data transfer |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
| CP_tdata_m[63:0]                                            | Out                                            | Comb, TF    | <b>To Coprocessor Data.</b> Data to be transferred to the coprocessor. For single word transfers, data is valid on CP_tdata_m[31:0]. Valid when CP_tds_m is asserted. Note: In 32 bit data transfer size configuration, this bus is reduced to CP_tdata_m[31:0].                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
| CP_tordlim_m[2:0]                                           | Sin                                            | Comb, TF    | <b>To Coprocessor Data Out-of-Order Limit.</b> This signal forces the integer processor core to limit how much it can reorder To COP data. The value on this signal corresponds to the maximum allowed value to be used on CP_torder_m[2:0].                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
| From Coprocessor Data (For all From Coprocessor Operations) |                                                |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
| CP_fds_m                                                    | In                                             | Comb, TF    | <b>Coprocessor From Data Strobe.</b> Asserted when From COP Op data is available on CP_fdata_m.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |
| CP_forder_m[2:0]                                            | In                                             | Comb, TF    | <b>Coprocessor From Order.</b> Specifies which outstanding From COP Op the data is for. Valid only when CP_fds_m is asserted.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                |       |        |                                            |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |        |                                                |

| Signal Name       | Dir  | Issue Group | Description                                                                                                                                                                                                                                                                                           |                                                  |
|-------------------|------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
|                   |      |             | <b>CP_forder_m</b>                                                                                                                                                                                                                                                                                    | <b>Order</b>                                     |
|                   |      |             | 3'b000                                                                                                                                                                                                                                                                                                | Oldest outstanding From COP Op data transfer     |
|                   |      |             | 3'b001                                                                                                                                                                                                                                                                                                | 2 <sup>nd</sup> oldest From COP OP data transfer |
|                   |      |             | 3'b010                                                                                                                                                                                                                                                                                                | 3 <sup>rd</sup> oldest From COP OP data transfer |
|                   |      |             | 3'b011                                                                                                                                                                                                                                                                                                | 4 <sup>th</sup> oldest From COP OP data transfer |
|                   |      |             | 3'b100                                                                                                                                                                                                                                                                                                | 5 <sup>th</sup> oldest From COP OP data transfer |
|                   |      |             | 3'b101                                                                                                                                                                                                                                                                                                | 6 <sup>th</sup> oldest From COP OP data transfer |
|                   |      |             | 3'b110                                                                                                                                                                                                                                                                                                | 7 <sup>th</sup> oldest From COP OP data transfer |
|                   |      |             | 3'b111                                                                                                                                                                                                                                                                                                | 8 <sup>th</sup> oldest From COP OP data transfer |
| CP_fdata_m[63:0]  | In   | Comb, TF    | <b>From Coprocessor Data.</b> Data to be transferred from coprocessor. For single-word transfers, data must be duplicated on both CP_fdata_m[63:32] and CP_fdata_m[31:0]. Valid when CP_fds_m is asserted. Note: In 32 bit data transfer size configuration, this bus is reduced to CP_fdata_m[31:0]. |                                                  |
| CP_fordlim_m[2:0] | Sout | Comb, TF    | <b>From Coprocessor Data Out-of-Order Limit.</b> This signal forces the coprocessor to limit how much it can reorder From COP Data. The value on this signal corresponds to the maximum allowed value to be used on CP_forder_m[2:0]                                                                  |                                                  |

Referring now to Figure 7, a block diagram 700 is shown illustrating particular data transfer signals 716 between a CPU 702 and a coprocessor 710 that were summarized above in Table 2. Each of the CPU 702 and the coprocessor 710 contain a COP interface 712 according to the present invention to allow data transfer as follows.

The coprocessor interface 712 within the CPU 702 transfers data to the coprocessor 710 after a TO

coprocessor data transfer instruction has been dispatched. Only TO coprocessor data transfer instructions utilize this transfer. The coprocessor 710 must have a buffer available for this data after the To coprocessor data transfer instruction has been dispatched. If no buffers are available, the coprocessor 710 must prevent instruction dispatch by asserting CPx\_tbusy\_m.

The coprocessor interface 712 allows out-of-order data transfers. That is, data can be sent by the CPU 702 to the coprocessor 710 in a different order from the order in which instructions were dispatched. When data is sent to the coprocessor 710, the CP\_torder\_m[2:0] signal group is also sent. This signal group tells the coprocessor 710 if the data word is for the oldest outstanding To coprocessor data transfer instruction, or the 2<sup>nd</sup> oldest, or the 3<sup>rd</sup> oldest, and so on. The coprocessor interface 712 allows up to 7 transfers to be outstanding while returning data for the next transfer. The coprocessor 710 can limit the extent of this reordering to match what its hardware supports, by using the CP\_tordlim\_m[2:0] signal group.

### ***To Coprocessor Data Transfer***

Referring to Figure 8, a timing diagram is shown illustrating data transferred from the CPU 702 to the

A6 coprocessor 710 via the coprocessor interface 712 of the present invention.

During clock cycles 2, 4, and 6, To coprocessor data transfer instructions A, B, and C are dispatched by the  
 5 coprocessor interface 712. These instruction transfers are completed with the assertion of the strobe signal CPx\_ts\_m in the following respective clock cycles.

During clock cycle 4, data corresponding to instruction A is presented on the signal group  
 10 CP\_tdata\_m[63:0]. In the same clock cycle the data transfer is completed by assertion of strobe signal CP\_tds\_m. In addition, the relative order of the data being transmitted on the signal group CP\_tdata\_m is provided by the signal group CP\_torder\_m[2:0]. In this  
 15 instance, since there are no outstanding To coprocessor data transfer instructions, the relative order of the data is "0".

During clock cycle 7, data corresponding to outstanding To coprocessor data transfer instruction C is  
 20 presented on signal group CP\_tdata\_m[63:0]. In addition, the data transfer is completed by assertion of strobe signal CP\_tds\_m. At this point, the data presented during clock cycle 7 is out-of-order with respect to its corresponding instruction C. That is, the data



corresponding to instruction B has not yet been presented. This fact is communicated by the CPU 702 via signal group CP\_torder\_m when it presents a value of "1" on its signal lines. When the coprocessor interface 712 within the  
5 coprocessor 710 sees the "1" value on this signal group, it understands that the data being received is to be associated with the 2<sup>nd</sup> oldest outstanding data transfer instruction, which in this case is instruction C.

During clock cycle 8, data associated with instruction  
10 B is presented on signal group CP\_tdata\_m. In addition, the data transfer is completed by assertion of strobe signal CP\_tds\_m. Finally, the relative order of the data being presented is provided via signal group CP\_torder\_m. In this instance, since the data associated with  
15 instruction A has already been provided, the data associated with instruction B is the oldest outstanding data. The coprocessor interface 712 within the CPU 702 therefore presents a value of "0" on signal group CP\_torder\_m.

20 Although not shown, what should be appreciated from the above is that out-of-order data transfers are independently tracked by the coprocessor interface 712 of the present invention, for each coprocessor 710 that is

coupled to CPU 702, and for each issue group within each coprocessor 710.

### ***From Coprocessor Data Transfer***

The coprocessor interface 712 of the present invention  
 5 transfers data from the coprocessor 710 to the CPU 702  
 after a From coprocessor data transfer instruction has been  
 dispatched. Only From transfer instructions utilize this  
 transfer. The CPU 702 must have available buffers to allow  
 the transfer to occur in the cycle after dispatch. The  
 10 coprocessor interface 712 allows out-of-order transfer of  
 data similar to that described above with reference to To  
 coprocessor data transfers.

Referring now to Figure 9, a timing diagram 900 is  
 shown illustrating the out-of-order data tracking mechanism  
 15 associated with From coprocessor data transfer  
 instructions, according to the coprocessor interface 712 of  
 the present invention.

During clock cycles 2-4, and 6, From data transfer  
 instructions A, B, C, and D are dispatched by the CPU 702  
 20 to the coprocessor 710. During clock cycles 3-5, and 7,  
 instructions A-D are transferred to coprocessor 710.

During clock cycle 4, data associated with instruction  
 A is presented by the coprocessor 710 to the CPU 702 via

signal group CP\_fdata\_m. The data transfer is completed by  
assertion of strobe signal CPx\_fds\_m during the same clock  
cycle. At this point, the data being presented corresponds  
to data instruction A, which is the oldest outstanding From  
5 data transfer. Therefore, the relative order of the data  
is provided by the coprocessor interface 712 within the  
coprocessor 710, indicated on signal group CP\_forder\_m as  
"0".

During clock cycle 5, data associated with instruction  
10 C is presented by the coprocessor 710 to the CPU 702. The  
data transfer is completed by assertion of strobe signal  
CP\_fds\_m during the same cycle. At this point, the data  
being presented corresponds to instruction C, which is the  
2<sup>nd</sup> oldest outstanding From data transfer, B data being the  
15 oldest. Therefore, the relative order of the data is  
provided by the coprocessor interface 712 within the  
coprocessor 710, indicated on signal group CP\_forder\_m as  
"1".

During clock cycle 7, data associated with instruction  
20 D is presented by the coprocessor 710 to the CPU 702. The  
data transfer is completed by assertion of strobe signal  
CP\_fds\_m during the same cycle. At this point, the data  
being presented corresponds to instruction D, which is the  
2<sup>nd</sup> oldest outstanding From data transfer, B being the

oldest. Therefore, the relative order of the data is provided by the coprocessor interface 712 within the coprocessor 710, indicated on signal group CP\_forder\_m as "1".

5 During clock cycle 8, data associated with instruction B is presented by the coprocessor 710 to the CPU 702. The data transfer is completed by assertion of strobe signal CP\_fds\_m during the same cycle. At this point, the data being presented corresponds to instruction B, which is the  
10 oldest outstanding From data transfer. Therefore, the relative order of the data is provided by the coprocessor interface 712 within the coprocessor 710, indicated on signal group CP\_forder\_m as "0".

Although not shown, what should be appreciated from  
15 the above is that out-of-order data transfers are independently tracked by the coprocessor interface 712 of the present invention, for each coprocessor 710 that is coupled to CPU 702, and for each issue group within each coprocessor 710.

20 **Condition Code Checking**

The coprocessor interface of the present invention provides signals for transferring the result of a condition code check from the coprocessor to the CPU. The

instructions that typically utilize condition codes include branch instructions and conditional move instructions. When these instructions are decoded by the CPU, they are dispatched to both the CPU and to the coprocessor.

5        Table 3 below provides a brief summary of the condition code check signals that are provided within the COP interface of the present invention. Illustration of how these signals operate will be further described below with reference to Figure's 10-11.

10

**TABLE 3**

| Signal Name | Dir | Issue Group | Description                                                                                                                                                                                                                                                                                                                   |
|-------------|-----|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CP_cccs_m   | In  | Comb, Arith | <b>Coprocessor Condition Code Check Strobe.</b> Asserted when condition code check results are available on CP_ccc_m.                                                                                                                                                                                                         |
| CP_ccc_m    | In  | Comb, Arith | <b>Coprocessor Condition Code Check.</b> Valid when CP_cccs_m is asserted. When asserted, the instruction checking the condition code should proceed with its execution (i.e., branch or move data). When deasserted, the instruction should not execute its conditional operation (i.e., do not branch and do not move data) |

For some instructions that are dispatched, a result is sent from the coprocessor to the CPU that indicates whether or not the CPU should execute that instruction. For branches, the coprocessor tells the CPU whether or not to branch. For example, a conditional branch executing in the CPU might require the evaluation of an operation whose operands occur within the coprocessor. In this instance,

the evaluation of the operation is performed entirely within the coprocessor, and providing the final condition codes to the CPU, rather than transferring the operands from the coprocessor to the CPU, and evaluating the result  
5 in the CPU.

In the same way, if a conditional move instruction requires evaluation of an operation whose operands occur within the coprocessor, rather than transferring the operands from the coprocessor to the CPU, and then  
10 evaluating the result, evaluation of the operation is performed entirely within the coprocessor. That is, for conditional moves, the coprocessor tells the CPU whether or not to execute the move instruction.

Thus, within the coprocessor interface of the present  
15 invention, it is the coprocessor that interprets certain conditional branch and conditional move instructions, and decides whether or not the CPU should execute them. Since evaluation of CPU branch and conditional move instructions are performed in the coprocessor, user-defined Boolean  
20 conditional operations are possible for conditional branch, and conditional move instructions, i.e., they need not be fixed a priori by the integer core.

Referring now to Figure 10, a block diagram 1000 is provided that illustrates the condition code signals 1016

transmitted by a coprocessor 1010 to a CPU 1002 via a coprocessor interface 1012. Operation of the condition code signals will now be described with reference to Figure 11, to which attention is now directed.

5        Figure 11 provides a timing diagram 1100 illustrating execution of three instructions, A, B, and C by the CPU 1002 and coprocessor 1010. Instruction A is dispatched by the CPU 1002 during clock cycle 2, and transfer is completed to the coprocessor 1010 by assertion of  
10    arithmetic strobe CPx\_as\_m during clock cycle 3. As mentioned above, instruction A also proceeds down the pipeline of the CPU 1002.

During clock cycle 4, the coprocessor interface 1012 of the coprocessor 1010 asserts the condition code strobe  
15    CP\_cccs\_m to indicate that the condition code resulting from evaluation of instruction A is available on condition code signal line CP\_ccc\_m. In this instance, CP\_ccc\_m is deasserted indicating to the CPU 1002 that it should not  
20    perform the operation specified by instruction A (either a conditional branch, or a conditional move operation).

Also during clock cycle 4, instruction B transfer is completed to the coprocessor 1010 by assertion of the arithmetic strobe CPx\_as\_m.

5

CO

15

th



condition codes exist for each issue group within a coprocessor's interface.

### ***GPR Data***

The coprocessor interface of the present invention provides signals for transferring the results of a check on a register within the CPU 1002 to the coprocessor 1010, for particular coprocessor instructions. These instructions include the MOVN.fmt and MOVZ.fmt instructions of the MIPS Instruction Set Architecture (ISA). Other instructions supported include the ALNV.PS and ALNV.fmt instructions. When these instructions are dispatched to the coprocessor 1010, they are also dispatched to the CPU 1002.

Table 4 below provides a brief summary of the GPR signals that are provided within the COP interface of the present invention.

TABLE 4

| Signal Name    | Dir                                                  | Issue Group | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                |                                          |                |                                     |              |                                                      |   |       |   |       |
|----------------|------------------------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|------------------------------------------|----------------|-------------------------------------|--------------|------------------------------------------------------|---|-------|---|-------|
| CPx_gprs_m     | Out                                                  | Comb, Arith | <b>GPR Strobe.</b> Asserted when additional general-purpose register information is available on CPx_gpr_m.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                |                                          |                |                                     |              |                                                      |   |       |   |       |
| CPx_gpr_m[3:0] | Out                                                  | Comb, Arith | <b>GPR Data.</b> Supplies additional data from the CPU general purpose register file. CPx_gpr_m[2:0] is valid when CPx_gprs_m is asserted and only for ALNV.PS and ALNV.fmt instructions. CPx_gpr_m[3] is valid when CPx_gprs_m is asserted and only for MOVN.fmt and MOVZ.fmt instructions. <table><tr><td>CPx_gpr_m[2:0]</td><td>RS<br/>(Valid only for ALNV.PS, ALNV.fmt)</td></tr><tr><td>Binary encoded</td><td>Lower 3bits of RS register contents</td></tr></table><br><table><tr><td>CPx_gpr_m[3]</td><td>RT Zero Check<br/>(Valid only for MOVN.fmt, MOVZ.fmt)</td></tr><tr><td>0</td><td>RT!=0</td></tr><tr><td>1</td><td>RT==0</td></tr></table> | CPx_gpr_m[2:0] | RS<br>(Valid only for ALNV.PS, ALNV.fmt) | Binary encoded | Lower 3bits of RS register contents | CPx_gpr_m[3] | RT Zero Check<br>(Valid only for MOVN.fmt, MOVZ.fmt) | 0 | RT!=0 | 1 | RT==0 |
| CPx_gpr_m[2:0] | RS<br>(Valid only for ALNV.PS, ALNV.fmt)             |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                |                                          |                |                                     |              |                                                      |   |       |   |       |
| Binary encoded | Lower 3bits of RS register contents                  |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                |                                          |                |                                     |              |                                                      |   |       |   |       |
| CPx_gpr_m[3]   | RT Zero Check<br>(Valid only for MOVN.fmt, MOVZ.fmt) |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                |                                          |                |                                     |              |                                                      |   |       |   |       |
| 0              | RT!=0                                                |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                |                                          |                |                                     |              |                                                      |   |       |   |       |
| 1              | RT==0                                                |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                |                                          |                |                                     |              |                                                      |   |       |   |       |

### Coprocessor Exception Found

The coprocessor interface of the present invention provides signals for transferring exception information from the coprocessor to the CPU. The exception found transfer is used to signal whether an instruction caused an exception in the coprocessor 1010, or not.

When a coprocessor instruction causes an exception, the coprocessor 1010 signals this to the CPU 1002 so that it can start execution from the exception vector.

Table 5 below provides a brief summary of the exception found signals that are provided within the COP interface of the present invention. Illustration of how these signals operate will be further described below with reference to Figure's 10 and 12.

**TABLE 5**

| Signal Name       | Dir | Issue Group     | Description                                                                                                                                                                                                                                                                   |                                           |
|-------------------|-----|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| CP_excfs_m        | In  | Comb, Arith, TF | <b>Coprocessor Exception Found Strobe.</b> Asserted when coprocessor exception signaling is available on CP_excfs_m.                                                                                                                                                          |                                           |
| CP_excfs_m        | In  | Comb, Arith, TF | <b>Coprocessor Exception Found.</b> When deasserted, the coprocessor is not causing an exception. When asserted, signifies that the coprocessor is causing an exception. The type of exception is encoded on the signal CP_exccode_m[4:0]. Valid when CP_excfs_m is asserted. |                                           |
| CP_exccode_m[4:0] | In  | Comb, Arith, TF | <b>Coprocessor Exception Code.</b> Valid when CP_excfs_m is asserted and CP_excfs_m is asserted.                                                                                                                                                                              |                                           |
|                   |     |                 | CP_exccode_m                                                                                                                                                                                                                                                                  | Exception                                 |
|                   |     |                 | 5'b01010                                                                                                                                                                                                                                                                      | Reserved Instruction Exception            |
|                   |     |                 | 5'b01111                                                                                                                                                                                                                                                                      | Floating Point Exception                  |
|                   |     |                 | 5'b10000                                                                                                                                                                                                                                                                      | Available for implementation specific use |
|                   |     |                 | 5'b10001                                                                                                                                                                                                                                                                      | Available for implementation specific use |
|                   |     |                 | 5'b10010                                                                                                                                                                                                                                                                      | COP2 Exception                            |
|                   |     |                 | Other values                                                                                                                                                                                                                                                                  | Reserved.                                 |

Referring now to Figure 12, a timing diagram 1200 is shown illustrating the exception found signal generation

provided by the coprocessor interface 1012 of the present invention.

Arithmetic instructions are dispatched by the CPU 1002 during clock cycles 2, 3 and 5. These instructions are transferred to the coprocessor 1010 by assertion of the arithmetic strobe signal CPx\_as\_m during clock cycles 3, 4 and 6, respectively.

For each of the instructions A, B, and C, exception found signals must be generated by the coprocessor 1010 to inform the CPU 1002 either that no exception occurred for the instruction, or that an exception occurred, along with an indication of the type of exception.

During clock cycle 4, the coprocessor interface 1012 within the coprocessor 1010 asserts exception found strobe CP\_excfs\_m to indicate that a coprocessor exception signal is available on CP\_excfs\_m.

Also during clock cycle 4, the exception signal CP\_excfs\_m is deasserted, thereby indicating that the oldest instruction for which an exception found signal has not been seen, in this case instruction A, did not generate an exception.

During clock cycle 5, the coprocessor interface 1012 within the coprocessor 1010 continues to assert exception

found strobe CP\_excfs\_m to indicate that a coprocessor exception found signal is available on CP\_excfs\_m.

Also during clock cycle 5, the exception signal CP\_excfs\_m is deasserted, thereby indicating that the oldest  
5 instruction for which an exception found signal has not been seen, in this case instruction B, did not generate an exception.

During clock cycle 8, the coprocessor interface 1012 within the coprocessor 1010 asserts exception found strobe  
10 CP\_excfs\_m to indicate that a coprocessor exception found signal is available on CP\_excfs\_m.

Also during clock cycle 8, the exception signal CP\_excfs\_m is asserted, indicating that the oldest  
instruction for which an exception found signal has not  
15 been seen, in this case instruction C, did generate an exception.

Furthermore, the coprocessor interface 1012 within the coprocessor 1010 generates an exception code on the signal group CP\_exccode\_m[4:0], to indicate to the CPU 1002 what  
20 type of exception was generated by instruction C in the coprocessor.

### Instruction Commit

The coprocessor interface of the present invention provides signals for notifying the coprocessor when instructions can or cannot commit state. All instructions  
 5 dispatched utilize this transfer so that the coprocessor knows when it can write back results for the instruction.

Table 6 below provides a brief summary of the instruction commit signals that are provided within the COP interface of the present invention. Illustration of how  
 10 these signals operate will be further described below with reference to Figure's 10 and 13.

**TABLE 6**

| Signal Name      | Dir | Issue Group     | Description                                                                                   |                                                      |
|------------------|-----|-----------------|-----------------------------------------------------------------------------------------------|------------------------------------------------------|
| CP_commits_m     | Out | Comb, Arith, TF | <b>Coprocessor Commit Strobe.</b> Asserted when commit signaling is available on CP_commit_m. |                                                      |
| CP_commit_m[1:0] | Out | Comb, Arith, TF | <b>Commit Coprocessor Instruction.</b> Valid when CP_commits_m is asserted.                   |                                                      |
|                  |     |                 | <b>CP_commit_m[1:0]</b>                                                                       | <b>Type of Commit / Kill</b>                         |
|                  |     |                 | 2'b00                                                                                         | Instruction is not killed and can commit its results |
|                  |     |                 | 2'b01                                                                                         |                                                      |
|                  |     |                 | 2'b10                                                                                         | Instruction is killed.<br>(not due to CP_exc_f_m)    |
|                  |     |                 | 2'b11                                                                                         | Instruction is killed<br>(due to CP_exc_f_m)         |

5 Occasionally, a coprocessor instruction will be killed because of a coprocessor signaled exception. For example, if a floating point instruction is killed because of a floating point exception, the coprocessor must update exception status bits in the coprocessor's status register. On the other hand, if that same instruction was killed because of a higher-priority exception, those status bits must not be updated. For this reason, as part of the commit when signaling a kill, the CPU 1002 tells the coprocessor if the instruction was killed due to a coprocessor signaled exception or not.

20 killed instruction(s) may affect the operation of subsequent instructions. In the cycle in which an instruction is killed, other transfers may occur, but after that cycle, no further transfers occur for any of the killed instructions. A side-effect of this is that

instructions subsequent to a killed instruction do not have a commit transfer of their own. In effect, they are immediately killed and thus their remaining transfers cannot be sent, including their own commit transfer.

5 Previously nullified instructions do not have a commit transfer either, because once nullified, no further transfers occur for that instruction.

Referring to Figure 13, a timing diagram 1300 is provided to particularly illustrate the instruction commit  
10 mechanism in the coprocessor interface of the present invention. Arithmetic instructions A, B, and C are dispatched by the CPU 1002 in clock cycles 2, 3, and 5, respectively. These instruction transfers are completed by the processor 1002 by assertion of the arithmetic strobe  
15 CPx\_as\_m during clock cycles 3, 4, and 6, respectively. Instruction commit information is then required for each of the instructions before the coprocessor is allowed to commit state.

During clock cycle 4, the commit strobe signal  
20 CP\_commits\_m is asserted by the coprocessor interface 1012 within the CPU 1002. This signal indicates that commit signaling is available on signal group CP\_commit\_m. Also during clock cycle 4, commit information is presented on signal group CP\_commit\_m by the coprocessor interface 1012



within the CPU 1002. The commit information presented on  
signal group CP\_commit\_m corresponds to the oldest  
instruction for which commit information has not yet been  
presented. In this case, the commit information  
5 corresponds to arithmetic instruction A.

In cycles 5 and 8, commit information associated with  
instructions B and C is presented on signal group  
CP\_commit\_m. Depending on the values presented on the  
signal group by the coprocessor interface 1012, the  
10 coprocessor 1010 will either commit or kill the associated  
instruction, according to the signal values shown in Table  
6.

#### ***Miscellaneous Interface Signals***

Table 7 below provides operational information  
15 relating to coprocessor interface signals that have not yet  
been discussed, but whose understanding is not enhanced by  
reference to a timing diagram.

TABLE 7

| Signal Name     | Dir | Issue Group     | Description                                                                                                                                                                                                                                                                                                                                                              |
|-----------------|-----|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CP_reset        | Out | None            | <b>Coprocessor Reset.</b> Asserted when a hard or soft reset is performed by the CPU. At a minimum, this signal will be asserted for 1 cycle.                                                                                                                                                                                                                            |
| CP_idle         | In  | None            | <b>Coprocessor Idle.</b> Asserted when the coprocessor logic is idle. Enables the integer processor core to go into sleep mode and shut down the internal integer processor core clock. Valid only if CP1_fppresent, CP1_mdmxpresent, or CPx_present is asserted.                                                                                                        |
| CP_tx32         | SIn | None            | <b>Coprocessor 32bit Transfers.</b> When asserted, the integer unit must cause an RI exception for 64bit TF instructions. Furthermore, when asserted, CP1_fppresent and CP1_mdmxpresent are ignored and internally deasserted. This forces CP_tx32 to only be used for COP2. This is a static input and must always be valid.                                            |
| CP1_fppresent   | Sin | None            | <b>Coprocessor FPU Present.</b> Must be asserted when FPU hardware is connected to the coprocessor interface.                                                                                                                                                                                                                                                            |
| CP1_mdmxpresent | Sin | None            | <b>Coprocessor MDMX Present.</b> Must be asserted when MDMX hardware is connected to the coprocessor interface.                                                                                                                                                                                                                                                          |
| CPx_present     | Sin | None            | <b>Coprocessor Present.</b> Must be asserted when coprocessor hardware is connected to the coprocessor interface.                                                                                                                                                                                                                                                        |
| CP_irenable_m   | Out | Comb, Arith, TF | <b>Enable Instruction Registering.</b> When deasserted, no instruction strobes will be asserted in the following cycle. When asserted, there may be an instruction strobe asserted in the following cycle. Instruction strobes include CPx_as_m, CPx_ts_m, CPx_fs_m.                                                                                                     |
| CP_adisable_m   | Sin | Comb, Arith     | <b>Inhibit Arithmetic Dispatch.</b> When asserted, prevents the CPU from dispatching an arithmetic instruction using this issue group.                                                                                                                                                                                                                                   |
| CP_tfdisable_m  | Sin | Comb, TF        | <b>Inhibit To/From Dispatch.</b> When asserted, prevents the CPU from dispatching a To/From instruction using this issue group.                                                                                                                                                                                                                                          |
| CP_inst32_m     | Out | Comb, Arith, TF | <b>MIPS32 Compatibility Mode – Instructions.</b> When asserted, the dispatched instruction is restricted to the MIPS32 subset of instructions. Please refer to the MIPS64 architecture specification available from MIPS Technologies, Inc. for a complete description of MIPS32 compatibility mode. Valid the cycle before CPx_as_m, CPx_fs_m, or CPx_ts_m is asserted. |

| Signal Name | Dir | Issue Group     | Description                                                                                                                                                                                                                                                              |
|-------------|-----|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CP_fr32_m   | Out | Comb, Arith, TF | <b>MIPS32 Compatibility Mode - Registers.</b> When asserted, the dispatched instruction uses the MIPS32 compatible register file. Valid the cycle before CPx_as_m, CPx_ts_m, or CPx_fs_m is asserted.                                                                    |
| CP_endian_m | Out | Comb, Arith, TF | <b>Big Endian Byte Ordering.</b> When asserted, the processor is using big endian byte ordering for the dispatched instruction. When deasserted, the processor is using little-endian byte ordering. Valid the cycle before CPx_as_m, CPx_ts_m, or CPx_fs_m is asserted. |

### *Various Issue Group Configurations*

A CPU that supports only single-issue integer instructions may implement a single combined issue group that can issue any type of instruction as follows:

The issue group will be 0 (m=0).

CP\_adisable\_0 and CP\_tfdisable\_0 may not be implemented. Since this is the only issue group, these instructions can never be disabled.

CP\_order\_0[2:0] may not be implemented. Since there is only one issue group, dispatch order is not needed.

An integer core with this configuration can be used with a coprocessor with more issue groups. In this case, the Combined issue group of the coprocessor is connected to the combined issue group of the integer processor core and the other issue groups of the coprocessor are tied inactive.

An integer processor core that supports limited dual issue supports dual-issue of instructions only when one is an arithmetic coprocessor instruction and the other is a To/From coprocessor instruction. With this option, two  
5 issue groups will be implemented - one combined (issue group 0) and one arithmetic (issue group 1).

An integer core that supports full dual issue supports all the cases of limited dual issue, plus it can issue two arithmetic instructions or two To/From instructions. With  
10 this option, two combined issue groups will be implemented.

A single-issue coprocessor can be used with a dual-issue integer processor core by simply connecting the combined issue groups together and asserting CP\_adisable\_1 and CP\_tfdisable\_1 for the 2<sup>nd</sup> combined issue group of the  
15 integer processor core.

A limited dual-issue coprocessor can be used with a dual-issue integer processor core by connecting the coprocessor combined issue group to one of the integer processor core's combined issue groups and asserting  
20 CP\_adisable\_m for that issue group. Then, connect the coprocessor's arithmetic issue group to the remaining combined issue group of the integer processor core and assert CP\_tfdisable\_m for that issue group.

Although the present invention and its objects, features, and advantages have been described in detail, other embodiments are encompassed by the invention. In addition to implementations of the invention using hardware, the invention can be embodied in software disposed, for example, in a computer usable (e.g., readable) medium configured to store the software (i.e., a computer readable program code). The program code causes the enablement of the functions or fabrication, or both, of the invention disclosed herein. For example, this can be accomplished through the use of general programming languages (e.g., C, C++, etc.), hardware description languages (HDL) including Verilog HDL, VHDL, AHDL (Altera Hardware Description Language) and so on, or other programming and/or circuit (i.e., schematic) capture tools available in the art. The program code can be disposed in any known computer usable medium including semiconductor memory, magnetic disk, optical disc (e.g., CD-ROM, DVD-ROM, etc.) and as a computer data signal embodied in a computer usable (e.g., readable) transmission medium (e.g., carrier wave or any other medium including digital, optical or analog-based medium). As such, the code can be transmitted over communication networks including the Internet and intranets. It is understood that the functions

accomplished and/or structure provided by the invention as described above can be represented in a core that is embodied in program code and may be transformed to hardware as part of the production of integrated circuits. Also,  
5 the invention may be embodied as a combination of hardware and software.

Furthermore, the particular illustrations used to describe the coprocessor interface of the present invention included a single CPU and a single coprocessor. However,  
10 as mentioned above, the coprocessor interface has been described to encompass connections between multiple CPU's and multiple coprocessors, any of which may have single issue pipelines, or multiple issue pipelines.

Also, although the coprocessor interface has been  
15 described with particular reference to MIPS32 and MIPS64 Instruction Set Architecture, one skilled in the art will appreciate that the scalability, and configurability of the interface is not limited to such architecture, nor is it limited to the data width of the instructions, and/or the  
20 data that is being transferred.

Finally, those skilled in the art should appreciate that they can readily use the disclosed conception and specific embodiments as a basis for designing or modifying

other structures for carrying out the same purposes of the present invention without departing from the spirit and scope of the invention as defined by the appended claims.

We claim:

006227 2425260